KUZCO

Comments

Elixir 22-in Chandelier


Model	Color Temperature	Wattage	Voltage	Total Lumens	Delivered Lumens	Dimmer Support (Optional, Not Included)
CH15504-UNV CH15504-BG-UNV CH15504-BK-UNV CH15504-CH-UNV	3000К	13W	120-277V	1055lm	780lm* (BG) 710lm* (BK) 850lm* (CH)	TRIAC/ELV




The Elixir collection combines opal glass globes with bold modern disks in effortlessly clean, striking forms. With its blend of organic shapes and minimal design, Elixir offers versatile configurations. Elixir can complement any aesthetic, from contemporary to transitional.

SPECIFICATION DETAILS

Fixture DimensionsL23-1/4" x W22-1/8" x H9-1/8"Canopy DimensionsD5-1/8" x H1-1/2"Minimum Hang Height18"LocationDryDimming Range100% - 10%Glass DetailsOpal GlassIllumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3x12" + 1x6" + 1x4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes CEC Title 24: Yes				
Minimum Hang Height18"LocationDryDimming Range100% - 10%Glass DetailsOpal GlassIllumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Fixture Dimensions	L23-1/4" x W22-1/8" x H9-1/8"		
LocationDryDimming Range100% - 10%Glass DetailsOpal GlassIllumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Canopy Dimensions	D5-1/8" x H1-1/2"		
Dimming Range100% - 10%Glass DetailsOpal GlassIllumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Minimum Hang Height	18"		
Glass DetailsOpal GlassIllumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Location	Dry		
Illumination DirectionOmni-directionalLight Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Dimming Range	100% - 10%		
Light Source/LifeLED (50,000 hours) 90CRIMaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Glass Details	Opal Glass		
MaterialSteel, GlassSlopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Illumination Direction	Omni-directional		
Slopped Ceiling AdaptableYes, 45 DegRod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Light Source/Life	LED (50,000 hours) 90CRI		
Rod Length46" Max (3×12" + 1×6" + 1×4")Shade DetailsSteel ShadeWire Length72"ComplianceETL Certified: Yes	Material	Steel, Glass		
Shade Details Steel Shade Wire Length 72" Compliance ETL Certified: Yes	Slopped Ceiling Adaptable	Yes, 45 Deg		
Wire Length 72" Compliance ETL Certified: Yes	Rod Length	46" Max (3×12" + 1×6" + 1×4")		
Compliance ETL Certified: Yes	Shade Details	Steel Shade		
	Wire Length	72"		
	Compliance			





FINISHES



* For custom options, contact customer service.

* For warranty information, please visit www.kuzcolighting.com/warranty

WWW.KUZCOLIGHTING.COM

USA: 3035 E. LONE MOUNTAIN ROAD - LAS VEGAS, NV 89081 CANADA: 19054 28TH AVENUE - SURREY, BC V3Z 6M3

© 2024 KUZCO LIGHTING. ALL RIGHTS RESERVED 20241210 Kuzco Lighting reserves the right to modify the design of our products at any time, as part of our ongoing commitment to continuous improvement.